

CLAIMS

1. A target detection system comprising:  
a radar;  
an image acquisition unit; and  
5 a processing unit for specifying an area  
of image recognition based on the data output from said  
radar and processing the image data output from said  
image acquisition unit only for said specified area.

2. A target detection system comprising:  
10 a radar for scanning a specified area and  
outputting signal of power corresponding to an object  
scanned;

an image acquisition unit for acquiring an  
image of said specified area; and

15 a processing unit for specifying an area  
of image recognition based on the power of the signal  
output from said radar, extracting the edge data from the  
image data output from said image acquisition unit only  
for said specified area, and detecting a target based on  
20 said edge data.

3. A target detection system according to claim 2,  
wherein said processing unit specifies an  
area having said power not less than a predetermined  
level as said image recognition area.

25 4. A target detection system according to claim 2,  
wherein said processing unit specifies an  
area having said power between a first predetermined  
level and a second predetermined level as said image  
recognition area.

30 5. A target detection system according to claim 2,  
wherein, in the case where the level of  
said power has a plurality of peaks, said processing unit  
specifies an area constituting a valley between the peaks  
as said image recognition area.

35 6. A target detection system according to claim 2,  
wherein said processing specifies as said  
image recognition area an area having said power not less

than a predetermined level, an area having said power between a first predetermined level and a second predetermined level, and an area constituting a valley between peaks in the case where the level of said power has a plurality of peaks.

5           7.    A target detection system according to claim 2,  
              wherein said processing unit extracts the peak position of the power of the signal output from said radar, checks the density change, on the left and right  
10   sides of said peak position, of the image data output from said image acquisition unit, extracts the position where the density change ceases to be laterally symmetric, and specifies an area having a predetermined width about said extraction position as said image  
15   recognition area.

          8.    A target detection system according to claim 2,  
              wherein said processing unit extracts the peak position of the power of the signal output from said radar, examines the density projection value, on the left  
20   and right sides of said peak position, of the image data output from said image acquisition unit, extracts the position where the density projection value ceases to be laterally symmetric, and specifies an area having a predetermined width about said extraction position as  
25   said image recognition area.

          9.    A target detection system comprising:  
              a radar for scanning a specified area and outputting signal of power corresponding to an object scanned;  
30               an image acquisition unit for acquiring an image of said specified area; and  
              a processing unit for extracting the edge data from the image data output from said image acquisition unit, specifying an area of image recognition  
35   based on the power of the signal output from said radar, and detecting a target using those of said extracted edge data existing in said specified area.

10. A target detection system according to claim 9,  
wherein said processing unit specifies an  
area having said power not less than a predetermined  
level as said image recognition area.

5 11. A target detection system according to claim 9,  
wherein said processing unit specifies an  
area having said power between a first predetermined  
level and a second predetermined level as said image  
recognition area.

10 12. A target detection system according to claim 9,  
wherein, in the case where the level of  
said power has a plurality of peaks, said processing unit  
specifies an area constituting a valley between the peaks  
as said image recognition area.

15 13. A target detection system according to claim 9,  
wherein said processing unit specifies, as  
said image recognition area an area having said power not  
less than a predetermined level, an area having said  
power between a first predetermined level and a second  
20 predetermined level, and an area constituting a valley  
between peaks in the case where the level of said power  
has a plurality of the peaks.

14. A target detection system comprising:  
a radar for outputting a near flag in the  
25 state corresponding to the distance upon determination  
that a target exists in a near area;  
an image acquisition unit for acquiring  
the image of a specified area; and  
an image recognition unit for outputting  
30 edge data by processing the image data output from said  
image acquisition unit;  
a processing unit for determining the  
state of the near flag output from said radar and  
detecting a target based on the edge data in the distance  
35 range corresponding to the state of said near flag among  
the edge data output from said image recognition unit.

15. A target detection system comprising:

a radar for outputting a near flag in the state corresponding to the distance upon determination that a target exists in a near area;

5 an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, removing and outputting the edge data in the distance range corresponding to the state of the near flag output from a processing unit; and

10

a processing unit for determining the state of the near flag output from said radar, outputting the result thereof to said image recognition unit, and detecting a target based on the edge data output from said image recognition unit.

15

16. A target detection system comprising:

a radar for outputting a near flag in the state corresponding to the distance upon determination that a target exists in a near area;

20

an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, performing the pattern matching processing in priority for the edge data within the distance range corresponding to the state of the near flag output from a processing unit, and outputting said edge data; and

25

a processing unit for determining the state of the near flag output from said radar, outputting the result thereof to said image recognition unit, and detecting a target based on the edge data output from said image recognition unit.

30

35 17. A target detection system comprising:

a radar for outputting a near flag in the state corresponding to the distance upon determination

2025 RELEASE UNDER E.O. 14176

that a target exists in a near area;

an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, outputting by attaching the road surface flag to the edge data identified as an edge of the road surface from the height information and the distance information obtained from said image data; and

a processing unit for determining the distance range corresponding to the state of the near flag output from said radar, invalidating the edge data output from said image recognition unit and having said road surface flag attached thereto, in the case where the distance information of said edge data with said road surface flag attached thereto indicates a near distance and said determined distance range indicates a far distance, and performing said target detection process based on the remaining edge data.

18. A target detection system comprising:

a radar for outputting distance information;

an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, outputting by attaching the road surface flag to the edge data identified as an edge of the road surface based on the height information and the distance information obtained from said image data; and

a processing unit for determining whether the distance information of the edge data output from said image recognition unit and having said road surface flag attached thereto is within the allowable error range of the distance information acquired from said radar, in

TECHNOLOGY

the case where said edge data with said road surface flag attached thereto indicates a far distance, and invalidates said edge data and performs the target detection process based on the remaining edge data in the case where said distance information is not within said allowable error range.

19. A target detection system comprising:

a radar for outputting a near flag in the state corresponding to the distance upon determination that a target exists in a near area;

an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, outputting by attaching a letter flag to the edge data identified as a letter on the road surface based on the density information obtained from said image data; and

a processing unit for determining the distance range corresponding to the state of the near flag output from said radar, invalidating the edge data output from said image recognition unit and having said letter flag attached thereto in the case where the distance information of the edge data with said letter flag attached thereto indicates a near distance and said determined distance range indicates a far distance, and performing said target detection process based on the remaining edge data.

20. A target detection system comprising:

a radar for outputting distance information;

an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, outputting by attaching a letter flag to the edge data

2025 RELEASE UNDER E.O. 14176

identified as a letter on the road surface based on the density information obtained from said image data; and

5 a processing unit for determining whether the distance information of the edge data output from said image recognition unit and having said letter flag attached thereto is within the allowable error range of the distance information acquired from said radar, in the case where said distance information of the edge data with said letter flag attached thereto indicates a far  
10 distance, and invalidating said edge data and performing the target detection process based on the remaining edge data in the case where said distance information is not within said allowable range.

21. A target detection system comprising:

15 a radar for outputting a near flag in the state corresponding to the distance upon determination that a target exists in a near area;

an image acquisition unit for acquiring the image of a specified area;

20 an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, outputting by attaching a road surface flag to the edge data identified as a letter on the road surface based on  
25 the height information and the distance information obtained from said image data, and also by attaching a letter flag to the edge data identified as a letter on the road surface based on the density information; and

30 a processing unit for determining the distance range corresponding to the state of the near flag output from said radar, and invalidating the edge data output from said image recognition unit and having at least one of said road surface flag and said letter flag attached thereto, in the case where the distance  
35 information of said edge data having at least one of said road surface flag and said letter flag attached thereto indicates a near distance and said determined distance

range indicates a far distance, and performing said target detection process based on the remaining edge data.

22. A target detection system comprising:

5 a radar for outputting a near flag in the state corresponding to the distance upon determination that a target exists in a near area;

an image acquisition unit for acquiring the image of a specified area;

10 an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, outputting by attaching a road surface flag to the edge data identified as a letter on the road surface based on the height information and the distance information  
15 obtained from said image data and also by attaching a letter flag to the edge data identified as a letter on the road surface based on the density information; and

20 a processing unit for determining whether the distance information of the edge data output from said image recognition unit and having at least one of said road surface flag and said letter flag attached thereto is within the allowable error range of the distance data obtained from said radar, in the case where  
25 the distance information of said edge data having at least one of said road surface flag and said letter flag attached thereto indicates a far distance, and invalidating said edge data having at least one of said road surface flag and said letter flag attached thereto  
30 and performing said target detection process based on the remaining edge data, in the case where said distance information is not within said allowable error range.

2025 RELEASE UNDER E.O. 14176